

DC to DC Converter

Features

- Input Voltage 9-36VDC; Output 18V, 24V or 48VDC
- IEEE 802.3af compliant model and non-compliant models
- Dual Inputs for connecting 2 power sources
- Integrated 10/100MB POE Inserter
- High Power up to 24W
- Low self consumption power
- Short Circuit, Over Current and Reverse/Over Voltage Protection
- High Temperature Operation
- Compact size – Maximize Available Space



TP-DCDC-12xx

Applications

- 12V / 24V Battery Systems
- Wireless Access Points and Client Devices
- IP Phone and Security Camera Systems



TP-DCDC-1248M
(Metal Enclosure)

Description

The TP-DCDC Series of DC to DC converters offered by Tycon Power Systems are a low cost and high reliability solution for those requiring 18V to 48VDC Power Over Ethernet voltage from a 12 or 24V battery system. They have an integrated POE injector to apply the 48VDC to the CAT5 Ethernet cable. The output is regulated 18V, 24V or 48VDC from an input voltage between 9VDC and 36VDC. They have two isolated inputs for connecting 2 power sources, like a primary and backup power source. A metal enclosure model is available for industrial applications.

They accept data-in to a shielded RJ45 Jack and provide data-out and POE power on the shielded RJ45 output jack. They work by supplying power on the unused Ethernet pins 4,5(V+) and 7,8(V-). An IEEE 802.3af compliant model is available for those applications requiring 802.3af handshake.

They have various protections for surge, short circuit and overload. The units have power output up to 24W.

If the remote device does not support power over Ethernet, splitters (POE-SPLT) are available to split the data and DC voltage at the remote device. If the remote device requires reverse voltage the POE-XOVER cable can be used.

Device Pinouts


RJ-45 Input (Data Only)			RJ-45 Output (Data & Power)	
Pin	Symbol	Description	Symbol	Description
1	RX+	Data Receive(+)	RX+	Data Receive(+)
2	RX-	Data Receive(-)	RX-	Data Receive(-)
3	TX+	Data Transmit(+)	TX+	Data Transmit(+)
4	NC	No Connection	+Vdc	DC power(+)
5	NC	No Connection	+Vdc	DC power(+)
6	TX-	Data Transmit(-)	TX-	Data Transmit(-)
7	NC	No Connection	-Vdc	DC power(-)
8	NC	No Connection	-Vdc	DC power(-)

Specifications

	TP-DCDC-1218	TP-DCDC-1224	TP-DCDC-1248 (M)	TP-DCDC-1248D
DC Input Voltage	9VDC – 36VDC	9VDC – 36VDC	9VDC – 36VDC	9VDC – 36VDC
DC Input Connector	Removeable Screw Type Compression Wire Terminal (12 AWG Max)			
DC Output Voltage (+/-2.5%)	18V (Passive)	24V (Passive)	48V (Passive)	48V (802.3af)
Data in & Data/POE Output Connector	RJ45 (Shielded)			
Output Current (max)	1.0A	0.8A	0.5A	0.5A
Output Power (max)	18W	19W	24W	24W
Self Consumption Power	1W			
Efficiency (min)	75%			
Line Regulation	1%			
Load Regulation	5%			
Ripple	1%			
Noise	1%			
EMC Standards	FCC Class B NE55022 Class B			
Safety Standards	UL1950, CSA 22.2 & TUV EN60950			
Operating Temperature	-30 to +60°C (-22 to +140°F)			
Operating Humidity (RH)	5% - 90%			
Storage Temperature	-40 to +80°C (-40 to +176°F)			
Dimensions (LxWxH)	85 x 76 x 36mm (3.4 x 3 x 1.4")			
Weight	134g (4.7oz)			

Notes:

- All shipments F.O.B. Bluffdale, UT 84065
- Tycon Power Systems Power Sources carry a 1 year warranty

DC Input Connector


System Ordering:

TP-DCDC-1218	9-36VDC IN 18VDC OUT, 18W DC to DC Converter with POE Inserter
TP-DCDC-1224	9-36VDC IN 24VDC OUT, 19W DC to DC Converter with POE Inserter
TP-DCDC-1248	9-36VDC IN 48VDC OUT, 24W DC to DC Converter with POE Inserter
TP-DCDC-1248M	9-36VDC IN 48VDC OUT, 24W DC to DC Converter with POE Inserter. Metal Case.
TP-DCDC-1248D	9-36VDC IN 48VDC OUT, 24W DC to DC Converter with 802.3af POE Inserter

POE-XOVER POE Voltage Crossover Cable - converts standard POE pin-out to reverse voltage pin-out

POE-SPLT Passive Splitter – 5.5/2.1mm DC Plug

POE-YSPLT Passive Y* Splitter – 5.5/2.1mm DC Plug
(*Power is supplied on both RJ45 and DC Plug)



For further information contact:

Tyconpower.com



693 Draper Heights Way Ste 102
Draper, UT 84020
PH: 801-750-3440
FAX: 801-501-7464